

**AUSTIN GIPSY GIPSY G4M10/15 (1964-1968)****ENGINE**

Capacity: 5,25 liter, Filter capacity: 0,7 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Classic Multigrade 10W-30***Change every 10000 km/ 6 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Classic Monograde 30***Change every 10000 km/ 6 months***DIFFERENTIAL FRONT**

Capacity: 1,73 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Classic Gear EP 90***Check every 5000 km/ 3 months, change every 20000 km/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**Classic Gear EP 80***Check every 5000 km/ 3 months, change every 20000 km/ 12 months***DIFFERENTIAL REAR**

Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Classic Gear EP 90***Check every 5000 km/ 3 months, change every 20000 km/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**Classic Gear EP 80***Check every 5000 km/ 3 months, change every 20000 km/ 12 months*

**AUSTIN GIPSY GIPSY G4M10/15 (1964-1968)****TRANSAXLE MANUAL 4/1**

Capacity: 2,2 liter, Capacity: 2,4 liter (With tyre pump)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Classic Multigrade 10W-30</b>	<b>Classic Monograde 30</b>	

*Check every 5000 km/ 3 months, change every 20000 km/ 12 months***TRANSFERBOX**

Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Classic Multigrade 10W-30</b>	<b>Classic Monograde 30</b>	

*Check every 5000 km/ 3 months, change every 20000 km/ 12 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

*Check every 5000 km/ 3 months***HYDRAULIC CLUTCH SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

*Check every 5000 km/ 3 months***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 5000 km/ 3 months*

**AUSTIN GIPSY GIPSY G4M10/15 (1964-1968)****COOLING SYSTEM**

Capacity: 12 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

**STEERING BOX**

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Classic Gear EP 90</b>		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
<b>Classic Gear EP 80</b>		

**SWIVEL HOUSING**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Classic Gear EP 90</b>		

*Check every 5000 km/ 3 months*

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
<b>Classic Gear EP 80</b>		

*Check every 5000 km/ 3 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.