

PRODUCT RECOMMENDATION

AUTOBIANCHI A112 A112 JUNIOR (1979-1982)



ENGINE A112A5.000
Capacity: 3,9 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1		
Classic Monograde 50		

Change every 10000 km/ 6 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Racing Oil 15W-50	Classic Multigrade 20W-50	Classic Multigrade 15W-40

Change every 10000 km/ 6 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
HDX 10W		

Change every 10000 km/ 6 months

USE	CLIMATE
Severe	Tropical

PRODUCT RECOMMENDATION 1		
Classic Monograde 50		

Change every 5000 km/ 3 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Racing Oil 15W-50	Classic Multigrade 20W-50	Classic Multigrade 15W-40

Change every 5000 km/ 3 months

USE	CLIMATE
Severe	Arctic

PRODUCT RECOMMENDATION 1		
HDX 10W		

Change every 5000 km/ 3 months

AUTOBIANCHI A112 A112 JUNIOR (1979-1982)



TRANSAXLE FRONT 4/1

Capacity: 2,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear ZC 90		

Check every 10000 km, change every 30000 km

HYDRAULIC BRAKE SYSTEM

Capacity: 0,33 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

COOLING SYSTEM

Capacity: 5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 60000 km/ 24 months

STEERING BOX

Capacity: 0,14 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.