

BMC AUSTIN MORRIS J4 J4 DIESEL (1972-1974)

**ENGINE 15Z**

Capacity: 4,69 liter, Filter capacity: 0,71 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 5000 km/ 3 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30*Change every 5000 km/ 3 months***DIFFERENTIAL REAR**

Capacity: 1,13 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 10000 km/ 3 months, change every 20000 km/ 6 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 10000 km/ 3 months, change every 20000 km/ 6 months***TRANSMISSION AUTOMATIC 3/1**

Capacity: 6,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF F*Check every 10000 km/ 3 months*

BMC AUSTIN MORRIS J4 J4 DIESEL (1972-1974)



TRANSMISSION MANUAL 4/1

Capacity: 2,55 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 10000 km/ 3 months, change every 20000 km/ 6 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 10000 km/ 3 months, change every 20000 km/ 6 months*

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Change every 30000 km/ 18 months*

HYDRAULIC CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Change every 30000 km/ 18 months*

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

BMC AUSTIN MORRIS J4 J4 DIESEL (1972-1974)**COOLING SYSTEM**

Capacity: 6,82 liter (+ heater), Capacity: 6,25 liter (Without heater)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Coolant -26		

*Change every 12 months***STEERING BOX**

Capacity: 0,28 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

Check every 10000 km/ 3 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		

Check every 10000 km/ 3 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.