

BMW (EU) SERIE 6 E24 628 CSI (1979-1982)



MOTOR M30B28

Kapacitet: 5,75 liter, Filterkapacitet: 0,75 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1

Classic Monograde 50

Skift alle 7500 km

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Classic Racing Oil 15W-50

PRODUKTANBEFALING 2

Classic Multigrade 20W-50

PRODUKTANBEFALING 3

Classic Multigrade 15W-40

Skift alle 7500 km

DIFFERENTIALE BAG

Kapacitet: 1,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Classic Gear MP 90

Kontroller alle 15000 km, skift alle 30000 km

GEAR AUTOMATISK 3/1

Kapacitet: 2 liter (Servicepåfyldning)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 15000 km, skift alle 30000 km

GEAR MANUEL Getrag 260 5/1

Kapacitet: 1,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Classic Gear EP 80

Kontroller alle 15000 km, skift alle 30000 km

BMW (EU) SERIE 6 E24 628 CSI (1979-1982)



SELVSPÆRRENDE DIFFERENTIALE BAG

Kapacitet: 1,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Gear LS 90

Kontroller alle 15000 km, skift alle 30000 km

HYDRAULISK BREMSESYSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-S DOT 4

Kontroller alle 7500 km, skift alle 12 måneder

SERVOSTYRING SEPARAT SYSTEM

Kapacitet: 2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic ATF A

Kontroller alle 7500 km

KØLESYSTEM

Kapacitet: 12 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.