PRODUCT RECOMMENDATION

# BMW (EU) 1500, 1600, 1800, 2000 E8 2000 CS (1965-1969)

## ENGINE
Capacity: 4,25 liter

| USE | | CLIMATE |
|---|---|---|
| Severe | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Classic Multigrade 10W-30** | **Classic Monograde 30** | |

*Change every 3000 km*

| USE | | CLIMATE |
|---|---|---|
| Summer months | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Classic Multigrade 10W-30** | **Classic Monograde 30** | |

*Change every 6000 km*

## DIFFERENTIAL REAR
Capacity: 0,9 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Classic Gear MP 90** | | |

*Check every 12000 km*

## TRANSMISSION AUTOMATIC ZF 3HP-12/B 3/1
Capacity: 5 liter, Capacity: 1,5 liter (Refill)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Classic ATF A** | | |

*Check every 12000 km, change every 18000 km*

## TRANSMISSION MANUAL 4/1
Capacity: 1 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Classic Gear EP 80** | | |

*Check every 12000 km, change every 24000 km*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# BMW (EU) 1500, 1600, 1800, 2000 E8 2000 CS
(1965-1969)

## HYDRAULIC BRAKE SYSTEM

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Drauliquid DOT 3** | | |

*Check every 6000 km*

## GREASE POINTS/NIPPLES DRIVE SHAFT SLIDING JOINTS
Capacity: 0,18 liter (each)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Classic Gear MP 90** | | |

*Check every 12000 km, change every 24000 km*

## GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

*Change every 60000 km*

## COOLING SYSTEM
Capacity: 7 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Coolant -38 Organic NF** | **Coolant -26** | |

## STEERING BOX
Capacity: 0,3 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Classic Gear EP 90** | | |

*Check every 12000 km*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367