

BMW (EU) 3 SERIES E30 323i (1982-1984)**ENGINE M20B23**

Capacity: 4,25 liter, Filter capacity: 0,25 liter

USE		CLIMATE
Flexible (on board maintenance system)		Tropical
PRODUCT RECOMMENDATION 1		
Classic Monograde 50		

USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Racing Oil 15W-50	Classic Multigrade 20W-50	Classic Multigrade 15W-40

DIFFERENTIAL REAR

Capacity: 0,9 liter, Capacity: 1,3 liter (Dry fill)

USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		

TRANSMISSION AUTOMATIC ZF 4HP22 4/1

Capacity: 3 liter

USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

TRANSMISSION MANUAL 5/1

Capacity: 1,3 liter, Capacity: 1,5 liter (sport version)

USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		

**HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Change every 12 months

POWER STEERING SEPARATE SYSTEM

Capacity: 1,2 liter

USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

COOLING SYSTEM

Capacity: 10,5 liter, Capacity: 11 liter (+ airconditioning)

USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.