

BMW (EU) 6 SERIES E24 635 CSI WITH CATALYST (1985-1987)

**ENGINE**

Capacity: 5,75 liter, Filter capacity: 0,75 liter

USE

Flexible (on board maintenance system)

CLIMATE

Tropical

PRODUCT RECOMMENDATION 1**Classic Monograde 50****USE**

Flexible (on board maintenance system)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Racing Oil 15W-50****PRODUCT RECOMMENDATION 2****Classic Multigrade 20W-50****PRODUCT RECOMMENDATION 3****Classic Multigrade 15W-40****DIFFERENTIAL REAR**

Capacity: 1,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Gear MP 90****DIFFERENTIAL REAR LIMITED SLIP****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Gear LS 90****TRANSMISSION AUTOMATIC 4/1**

Capacity: 3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**ATF Dexron II-D****TRANSMISSION MANUAL Getrag 260 5/1**

Capacity: 1,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Gear EP 80**

BMW (EU) 6 SERIES E24 635 CSI WITH CATALYST (1985-1987)



TRANSMISSION MANUAL Getrag 265 5/1

Capacity: 1,5-1,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Change every 12 months

POWER STEERING SEPARATE SYSTEM

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

COOLING SYSTEM

Capacity: 12 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.