## CADILLAC (USA / CAN) ELDORADO ELDORADO (1964-1966)



ENGINE Capacity: 4,7 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 10W-30	Classic Monograde 30	

Change every 10000 km/2 months

DIFFERENTIAL REAR	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear EP 90	
Check every 10000 km	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Classic Gear EP 80	
Check every 10000 km	

DIFFERENTIAL REAR LIMITED SLIP	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear LS 90	
Charles avant 40000 km	-

Check every 10000 km

TRANSMISSION AUTOMATIC Hydra-Ma Capacity: 10,9 liter (Dry fill), Capacity: 8,5		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF A		
Check every 10000 km, change every 360	00 km/ 24 months	

## CADILLAC (USA / CAN) ELDORADO ELDORADO (1964-1966)



<b>TRANSMISSION AUTOMATIC</b> Turbo-Hydramatic THM400 3/1 Capacity: 10,5 liter, Capacity: 3,4 liter (Refill)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Classic ATF A		
Check every 10000 km, change every 36000	km/ 24 months	

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 10000 km	·

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic ATF A	
Check every 10000 km	'

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 10000 km/2 months	3	

COOLING SYSTEM Capacity: 16,3 liter, Capacity: 17,3 lit	er (+ airconditioning)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.