

# CADILLAC (USA / CAN) ELDORADO

## ELDORADO (1968-1969)

**ENGINE**

Capacity: 5,7 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Classic Multigrade 10W-30</b>	<b>Classic Monograde 30</b>

*Change every 10000 km/ 4 months***DIFFERENTIAL FRONT**

Capacity: 2,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>Classic Gear EP 90</b>	

*Check every 6 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	
<b>Classic Gear EP 80</b>	

*Check every 6 months***DIFFERENTIAL FRONT LIMITED SLIP**

Capacity: 2,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>Classic Gear LS 90</b>	

*Check every 6 months***TRANSMISSION AUTOMATIC** Turbo-Hydramatic THM400 3/1

Capacity: 4,7 liter (Refill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>Classic ATF A</b>	

*Check every 10000 km/ 4 months, change every 36000 km/ 24 months*

# CADILLAC (USA / CAN) ELDORADO

## ELDORADO (1968-1969)



### HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

Check every 10000 km/ 4 months

### POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Classic ATF A</b>		

Check every 10000 km/ 4 months

### COOLING SYSTEM

Capacity: 19,2 liter, Capacity: 19,4 liter (+ airconditioning)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

Check every 10000 km/ 4 months, change every 36000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.