

# CADILLAC (USA / CAN) SERIES 60 SERIES

## 60 (1959-1960)

**ENGINE**

Capacity: 5,6 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Classic Multigrade 10W-30**

## PRODUCT RECOMMENDATION 2

**Classic Monograde 30***Change every 6000 km/ 2 months***DIFFERENTIAL REAR**

Capacity: 2,4 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Classic Gear EP 90***Check every 6000 km*

## USE

Normal

## CLIMATE

Arctic

## PRODUCT RECOMMENDATION 1

**Classic Gear EP 80***Check every 6000 km***TRANSMISSION AUTOMATIC** Hydra-Matic 3/1

Capacity: 10,9 liter (Dry fill), Capacity: 8,5 liter (Refill)

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Classic ATF A***Check every 6000 km, change every 18000 km/ 12 months***HYDRAULIC BRAKE SYSTEM**

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Check every 6000 km, change every 12 months*

# CADILLAC (USA / CAN) SERIES 60 SERIES 60 (1959-1960)



## POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Classic ATF A</b>		

Check every 6000 km

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

Change every 6000 km/ 2 months

## COOLING SYSTEM

Capacity: 18,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.