

CHEVROLET (USA) CAMARO 1ST GEN

CAMARO 5.7L (1966-1969)

**ENGINE (350 CID)**

Capacity: 3,8 liter (Service fill)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Change every 6000 miles/ 4 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30*Change every 6000 miles/ 4 months*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Change every 3000 miles/ 2 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30*Change every 3000 miles/ 2 months***DIFFERENTIAL REAR**

Capacity: 1,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 5015*Check every 6000 miles/ 4 months***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 1,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear LS 90*Check every 6000 miles/ 4 months*

CHEVROLET (USA) CAMARO 1ST GEN

CAMARO 5.7L (1966-1969)



TRANSMISSION AUTOMATIC Powerglide 2/1
Capacity: 2 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 6000 miles/ 4 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Change every 24000 miles*

TRANSMISSION AUTOMATIC Turbo-Hydramatic 3/1
Capacity: 3,6 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Change every 24000 miles*

TRANSMISSION MANUAL 3/1
Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 5015*Check every 6000 miles/ 4 months*

TRANSMISSION MANUAL 4/1
Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 5015*Check every 6000 miles/ 4 months*

CHEVROLET (USA) CAMARO 1ST GEN

CAMARO 5.7L (1966-1969)



HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 6000 miles/ 4 months

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF A		

Check every 6000 miles/ 4 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 6000 miles/ 4 months

COOLING SYSTEM

Capacity: 15,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.