

CHEVROLET (USA) CAPRICE CAPRICE 396 (1961-1969)



ENGINE (396 CID)
Capacity: 3,8 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Monograde 30

Change every 10000 km/ 2 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30

Change every 10000 km/ 2 months

DIFFERENTIAL REAR

Capacity: 1,8 liter (Heavy Duty), Capacity: 1,4 liter (Standard)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 5015

Check every 2 months

DIFFERENTIAL REAR LIMITED SLIP

Capacity: 1,8 liter (Heavy Duty), Capacity: 1,4 liter (Standard)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear LS 90

Check every 2 months

TRANSMISSION AUTOMATIC Powerglide

Capacity: 1,2 liter (Refill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A

Check every 2 months, change every 36000 km

CHEVROLET (USA) CAPRICE CAPRICE 396 (1961-1969)


TRANSMISSION AUTOMATIC Powerglide HD 3/1

Capacity: 7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 2 months, change every 20000 km*
TRANSMISSION AUTOMATIC Turbo-Hydramatic 350 3/1

Capacity: 6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 2 months, change every 36000 km*
TRANSMISSION MANUAL 3/1

Capacity: 0,83 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 5015*Check every 2 months*
TRANSMISSION MANUAL 4/1

Capacity: 1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 5015*Check every 2 months*
HYDRAULIC BRAKE SYSTEM

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 10000 km/ 2 months*

CHEVROLET (USA) CAPRICE CAPRICE 396 (1961-1969)



POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF A		

Check every 2 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 10000 km

COOLING SYSTEM

Capacity: 17,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.