

CHEVROLET (USA) CORVETTE CORVETTE

(1961-1962)

**ENGINE (327 CID)**

Capacity: 5,7 liter

USE	CLIMATE
Ambient temperatures above 0°C	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Change every 6000 km/ 2 months*

USE	CLIMATE
Ambient temperatures above 0°C	Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30*Change every 6000 km/ 2 months*

USE	CLIMATE
Ambient temperatures below 0°C	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Change every 6000 km/ 1 months*

USE	CLIMATE
Ambient temperatures below 0°C	Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30*Change every 6000 km/ 1 months***DIFFERENTIAL REAR**

Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 1500 km***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear LS 90*Check every 1500 km*

CHEVROLET (USA) CORVETTE CORVETTE

(1961-1962)



TRANSMISSION AUTOMATIC Powerglide

Capacity: 10,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 1500 km*

TRANSMISSION MANUAL 3/1

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 1500 km*

TRANSMISSION MANUAL 4/1

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 1500 km*

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 1500 km*

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 1500 km*

CHEVROLET (USA) CORVETTE CORVETTE

(1961-1962)

**COOLING SYSTEM**

Capacity: 16,1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.