

CITROËN DS / ID DS 19 (1955-1961)**ENGINE**

Capacity: 4 liter

| USE | | CLIMATE |
|----------------------------------|-----------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Classic Multigrade 10W-30 | Classic Monograde 30 | |

*Change every 4000 km/ 6 months***TRANSAXLE MANUAL 4/1**

Capacity: 2 liter

| USE | | CLIMATE |
|---------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Classic Gear EP 90 | | |

*Check every 4000 km/ 6 months, change every 16000 km/ 24 months***HYDRAULIC SYSTEM**

Capacity: 5,2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

COOLING SYSTEM

Capacity: 11 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.