

DAF COMMERCIAL COMBI (1963-1967)



ENGINE 746
Capacity: 2 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Classic Multigrade 15W-40	Classic Monograde 30

Change every 5000 km/ 3 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Classic Multigrade 10W-30	

Change every 5000 km/ 3 months

FINAL DRIVES
Capacity: 140 CM3 (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Classic ATF A	

Change every 20000 km

POWER DIVIDER 1/1
Capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Classic ATF A	

Change every 20000 km

VARIOMATIC TRANSMISSION PRIMARY DISC
Capacity: 75 CM3

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Classic ATF A	

DAF COMMERCIAL COMBI (1963-1967)**VARIOMATIC TRANSMISSION SECONDARY DISC**

Capacity: 60 CM3

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF A		

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.