

FIAT (EU) 126 126 0.6 126A (1972-1978)



MOTOR 126A.000
Kapacitet: 2,5 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1

Classic Monograde 50

Kontroller alle 500 km, skift alle 10000 km/ 6 måneder

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Classic Racing Oil 15W-50

PRODUKTANBEFALING 2

Classic Multigrade 15W-40

Kontroller alle 500 km, skift alle 10000 km/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Classic Multigrade 10W-30

PRODUKTANBEFALING 2

Classic Monograde 30

Kontroller alle 500 km, skift alle 10000 km/ 6 måneder

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

HDX 10W

Kontroller alle 500 km, skift alle 10000 km/ 6 måneder

TRANSAKSEL MANUEL 4/1
Kapacitet: 1,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Classic Gear ZC 90

Kontroller alle 10000 km, skift alle 30000 km

HYDRAULISK BREMSESYSTEM
Kapacitet: 0,35 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

FIAT (EU) 126 126 0.6 126A (1972-1978)



SMØREPUNKTER/NIPLER HJULLEJER FOR

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

Skift alle 30000 km

STYREHUS

Kapacitet: 0,12 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Gear MP 90

Kontroller alle 10000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.