

PRODUCT RECOMMENDATION

FIAT (EU) 1300/1500(S)/1600S 115/116/118

1500 115 (1961-1967)



ENGINE 115(C).000
Capacity: 3,5 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1		
Classic Monograde 50		

Change every 10000 km/ 6 months

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Classic Multigrade 15W-40		

Change every 10000 km/ 6 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 10W-30	Classic Monograde 30	

Change every 10000 km/ 6 months

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1		
Classic Monograde 50		

Change every 1500 km

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1		
Classic Multigrade 15W-40		

Change every 1500 km

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 10W-30	Classic Monograde 30	

Change every 1500 km

USE	CLIMATE
Second change only	Tropical

PRODUCT RECOMMENDATION 1		
Classic Monograde 50		

Change every 4500 hours

FIAT (EU) 1300/1500(S)/1600S 115/116/118

1500 115 (1961-1967)



USE		CLIMATE
Second change only		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Multigrade 15W-40		

Change every 4500 hours

USE		CLIMATE
Second change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 10W-30	Classic Monograde 30	

Change every 4500 hours

DIFFERENTIAL REAR		
Capacity: 0,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		

Check every 10000 km, change every 30000 km

TRANSMISSION MANUAL 4/1		
Capacity: 1,35 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		

Check every 10000 km, change every 30000 km

HYDRAULIC BRAKE SYSTEM		
Capacity: 0,27 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 10000 km



FIAT (EU) 1300/1500(S)/1600S 115/116/118

1500 115 (1961-1967)



HYDRAULIC CLUTCH SYSTEM

Capacity: 0,22 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 10000 km*

GREASE POINTS/NIPPLES

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gear Grease EP 1*Change every 2500 km*

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Labora Grease*Change every 20000 km*

COOLING SYSTEM

Capacity: 6,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26

GENERATOR

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Labora Grease*Change every 30000 km*

FIAT (EU) 1300/1500(S)/1600S 115/116/118

1500 115 (1961-1967)



STARTER

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 30000 km

STEERING BOX

Capacity: 0,18 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.