

FIAT (EU) 132 132 1.8 132A (1974-1977)

**ENGINE** 132AC1.000

Capacity: 4 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Classic Monograde 50*Check every 500 km, change every 5000 km/ 3 months*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Racing Oil 15W-50

PRODUCT RECOMMENDATION 2

Classic Multigrade 15W-40*Check every 500 km, change every 5000 km/ 3 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30

PRODUCT RECOMMENDATION 2

Classic Monograde 30*Check every 500 km, change every 5000 km/ 3 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

HDX 10W*Check every 500 km, change every 5000 km/ 3 months*

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1

Classic Monograde 50*Change every 2500 km*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Racing Oil 15W-50

PRODUCT RECOMMENDATION 2

Classic Multigrade 15W-40*Change every 2500 km*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30

PRODUCT RECOMMENDATION 2

Classic Monograde 30*Change every 2500 km*

FIAT (EU) 132 132 1.8 132A (1974-1977)

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
HDX 10W		
<i>Change every 2500 km</i>		

DIFFERENTIAL REAR Capacity: 1,65 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		
<i>Check every 10000 km, change every 30000 km</i>		

TRANSMISSION AUTOMATIC 3/1 Capacity: 2,8 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
<i>Check every 5000 km, change every 40000 km/ 24 months</i>		

TRANSMISSION MANUAL 4/1 Capacity: 1,28 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
<i>Check every 10000 km, change every 30000 km</i>		

TRANSMISSION MANUAL 5/1 Capacity: 1,53 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
<i>Check every 10000 km, change every 30000 km</i>		



FIAT (EU) 132 132 1.8 132A (1974-1977)**HYDRAULIC BRAKE SYSTEM**

Capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 500 km***GREASE POINTS/NIPPLES DRIVE SHAFT JOINTS**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Grease EP 1*Change every 30000 km***GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease*Change every 30000 km***COOLING SYSTEM**

Capacity: 8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26*Check every 500 km, change every 60000 km/ 24 months***STEERING BOX**

Capacity: 0,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 10000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.