

# FORD EUROPE CAPRI MK III CAPRI 3.0

## (1976-1981)

**ENGINE HYF**

Capacity: 5 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 10000 km/ 6 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

PRODUCT RECOMMENDATION 2

**Emperol 10W-40**

PRODUCT RECOMMENDATION 3

**Bi-Turbo 15W-40***Change every 10000 km/ 6 months***DIFFERENTIAL REAR**

Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Classic Gear MP 90***Check every 20000 km/ 12 months***TRANSMISSION AUTOMATIC C3 3/1**

Capacity: 7,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Classic ATF F***Check every 20000 km/ 12 months***TRANSMISSION MANUAL N 5/1**

Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Classic Gear EP 90**

PRODUCT RECOMMENDATION 2

**Syngear 75W-90***Check every 20000 km/ 12 months*

# FORD EUROPE CAPRI MK III CAPRI 3.0

## (1976-1981)



### HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid-S DOT 4</b>		

Change every 60000 km/ 36 months

### POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

Check every 10000 km/ 6 months

### COOLING SYSTEM

Capacity: 9,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

Change every 60000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.