

FORD (USA) MUSTANG FIRST GEN

MUSTANG 3.3 (200 CI) (1967-1970)

**ENGINE (200 CID)**

Capacity: 4,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 2

Classic Multigrade 10W-30*Change every 10000 km/ 6 months/ 6000 miles***DIFFERENTIAL REAR**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 10000 km/ 6 months/ 6000 miles***DIFFERENTIAL REAR LIMITED SLIP**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear LS 90*Check every 10000 km/ 6 months/ 6000 miles***TRANSMISSION AUTOMATIC**

Capacity: 7,3-8,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF F*Check every 10000 km/ 6 months/ 6000 miles***TRANSMISSION MANUAL 3/1**

Capacity: 1-1,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 10000 km/ 6 months/ 6000 miles*

FORD (USA) MUSTANG FIRST GEN

MUSTANG 3.3 (200 CI) (1967-1970)



TRANSMISSION MANUAL 4-SPEED Ford 4/1 4/1

Capacity: 1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		

Check every 10000 km/ 6 months/ 6000 miles

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF F		

Check every 10000 km/ 6 months/ 6000 miles

COOLING SYSTEM

Capacity: 9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.