

**GLAS 1004/1204/1304 S 1204 (1963-1965)****ENGINE 120**

Capacity: 2,5 liter, Filter capacity: 0,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Classic Multigrade 10W-30</b>	<b>Classic Monograde 50</b>	<b>Classic Monograde 30</b>

*Change every 6000 km*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
<b>HDX 10W</b>		

*Change every 6000 km*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Classic Multigrade 10W-30</b>	<b>Classic Monograde 50</b>	<b>Classic Monograde 30</b>

*Change every 500 km*

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1		
<b>HDX 10W</b>		

*Change every 500 km*

USE	CLIMATE
Second change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Classic Multigrade 10W-30</b>	<b>Classic Monograde 50</b>	<b>Classic Monograde 30</b>

*Change every 3000 km*

USE	CLIMATE
Second change only	Arctic

PRODUCT RECOMMENDATION 1		
<b>HDX 10W</b>		

*Change every 3000 km*

**GLAS 1004/1204/1304 S 1204 (1963-1965)****DIFFERENTIAL REAR**

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Classic Gear ZC 90***Check every 6000 km, change every 24000 km*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Classic Gear ZC 90***Change every 500 km*

USE	CLIMATE
Second change only	Moderate

PRODUCT RECOMMENDATION 1

**Classic Gear ZC 90***Change every 3000 km***TRANSMISSION MANUAL 4/1**

Capacity: 1,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Classic Gear EP 80***Check every 6000 km, change every 24000 km*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Classic Gear EP 80***Change every 500 km*

USE	CLIMATE
Second change only	Moderate

PRODUCT RECOMMENDATION 1

**Classic Gear EP 80***Change every 3000 km*

**GLAS 1004/1204/1304 S 1204 (1963-1965)****HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

*Check every 6000 km*

**GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>	<b>Multi Purpose Grease 3</b>

*Change every 3000 km*

**WHEEL BEARINGS FRONT**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 24000 km*

**COOLING SYSTEM**

Capacity: 6,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

**STEERING HOUSE**

Capacity: 0,14 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Classic Gear EP 80</b>		

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*