

# HOLDEN TORANA LC TORANA LC 138 HC

(1969-1972)

**ENGINE 138 HC / 2250 HC**

Capacity: 4,26 liter, Filter capacity: 0,85 liter

USE	CLIMATE
Normal	Mediterranean

## PRODUCT RECOMMENDATION 1

**Classic Monograde 30***Change every 10000 km/ 2 months*

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Classic Multigrade 15W-40**

## PRODUCT RECOMMENDATION 2

**Classic Multigrade 10W-30***Change every 10000 km/ 2 months***DIFFERENTIAL REAR**

Capacity: 0,85 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Classic Gear MP 90***Check every 10000 km***TRANSMISSION AUTOMATIC 3/1**

Capacity: 3,35 liter (Dry fill), Capacity: 1,7 liter (Service fill)

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**ATF Dexron II-D***Check every 10000 km, change every 20000 km***TRANSMISSION MANUAL 3/1**

Capacity: 2,13 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Classic Gear MP 90***Check every 10000 km, change every 20000 km*

# HOLDEN TORANA LC TORANA LC 138 HC

## (1969-1972)



### TRANSMISSION MANUAL 4/1

Capacity: 1,14 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Classic Gear MP 90***Check every 10000 km*

### HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Check every 3200 km, change every 20000 km/ 12 months*

### GREASE POINTS/NIPPLES GENERAL

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2***Change every 20000 km/ 6 months*

### COOLING SYSTEM

Capacity: 10-10,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

PRODUCT RECOMMENDATION 2

**Coolant -26**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.