
## **HOLDEN TORANA LC TORANA LC 70.7 HC**





<b>ENGINE</b> 70.7 HC Capacity: 2,84 liter, Filter capacity: 0,28	liter		
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Classic Monograde 30			
Change every 10000 km/2 months			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Classic Multigrade 15W-40	Classic Multigrade 10W-30		
Change every 10000 km/2 months			

<b>DIFFERENTIAL REAR</b> Capacity: 0,85 liter		
USE	c	CLIMATE
Normal	N	Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		
Check every 10000 km	· · · · · · · · · · · · · · · · · · ·	

TRANSMISSION MANUAL 3/1 Capacity: 2,13 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	
Check every 10000 km, change every	

TRANSMISSION MANUAL 4/1 Capacity: 1,14 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	
Check every 10000 km	

## **HOLDEN TORANA LC TORANA LC 70.7 HC**

(1969-1972)



HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 3200 km, change every 20000 km/ 12 month	S

GREASE POINTS/NIPPLES GENERAL		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 20000 km/6 months

COOLING SYSTEM Capacity: 4,26-4,66 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.