

JAGUAR (EU) S-TYPE S-TYPE 3.8 (1963-1968)



MOTOR

Kapacitet: 6,8 liter

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

Classic Monograde 50

Skift alle 5000 km

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Multigrade 15W-40

PRODUKTANBEFALING 2

Classic Multigrade 10W-30

PRODUKTANBEFALING 3

Classic Monograde 30

Skift alle 5000 km

DIFFERENTIALE BAG

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Gear EP 90

Kontroller alle 5000 km, skift alle 20000 km

GEAR AUTOMATISK 3/1

Kapacitet: 8,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic ATF A

Kontroller alle 5000 km, skift alle 20000 km

GEAR MANUEL 4/1

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Gear EP 90

Kontroller alle 5000 km, skift alle 20000 km

JAGUAR (EU) S-TYPE S-TYPE 3.8 (1963-1968)



GEAR MANUEL MED OVERGEAR 4/1

Kapacitet: 2,25 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Gear EP 90

Kontroller alle 5000 km, skift alle 20000 km

HYDRAULISK BREMSESYSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

HYDRAULISK KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 12,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

STYREHUS

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.