

JAGUAR (EU) XK-SERIE XK 120 3.4 SE/MC (1951-1954)



MOTOR XK-I6

Kapacitet: 16,6 liter, Filterkapacitet: 3,1 liter

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

Classic Monograde 50

Skift alle 4000 km

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Classic Multigrade 10W-30

Skift alle 4000 km

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Monograde 30

Skift alle 4000 km

DIFFERENTIALE BAG

Kapacitet: 2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Gear MP 90

Kontroller alle 4000 km, skift alle 16000 km

GEAR MANUEL 4/1

Kapacitet: 1,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Multigrade 10W-30

PRODUKTANBEFALING 2

Classic Monograde 30

Kontroller alle 4000 km, skift alle 16000 km

JAGUAR (EU) XK-SERIE XK 120 3.4 SE/MC (1951-1954)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Kontroller alle 1 uge

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 4000 km

KØLESYSTEM

Kapacitet: 14,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

KARBURATORSPJÆLD

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Classic Multigrade 10W-30	Classic Monograde 30	

Kontroller alle 4000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.