

JAGUAR (EU) MARK 2 / 240/340 MK2 3.4 (1959-1967)

**ENGINE**

Capacity: 7,5 liter (Dry fill), Capacity: 6,25 liter (Service fill)

USE

Normal

CLIMATE

Tropical

PRODUCT RECOMMENDATION 1

Classic Monograde 50*Change every 4000 km*

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30*Change every 4000 km*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Change every 4000 km***DIFFERENTIAL REAR**

Capacity: 1,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 4000 km, change every 16000 km***TRANSMISSION AUTOMATIC 3/1**

Capacity: 8,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 2000 km, change every 16000 km*

JAGUAR (EU) MARK 2 / 240/340 MK2 3.4 (1959-1967)



TRANSMISSION MANUAL 4/1

Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 4000 km, change every 16000 km*

TRANSMISSION MANUAL WITH OVERDRIVE 4/1

Capacity: 2,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 4000 km, change every 16000 km*

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

HYDRAULIC CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

JAGUAR (EU) MARK 2 / 240/340 MK2 3.4 (1959-1967)

**COOLING SYSTEM**

Capacity: 12,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

STEERING BOX

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.