

JAGUAR (EU) S-TYPE S-TYPE 3.8 (1963-1968)



ENGINE

Capacity: 6,8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

Classic Monograde 50*Change every 5000 km*

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 2

Classic Multigrade 10W-30

PRODUCT RECOMMENDATION 3

Classic Monograde 30*Change every 5000 km*

DIFFERENTIAL REAR

Capacity: 1,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 5000 km, change every 20000 km*

TRANSMISSION AUTOMATIC 3/1

Capacity: 8,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 5000 km, change every 20000 km*

TRANSMISSION MANUAL 4/1

Capacity: 1,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 5000 km, change every 20000 km*

JAGUAR (EU) S-TYPE S-TYPE 3.8 (1963-1968)



TRANSMISSION MANUAL WITH OVERDRIVE 4/1

Capacity: 2,25 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Gear EP 90

Check every 5000 km, change every 20000 km

HYDRAULIC BRAKE SYSTEM

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

HYDRAULIC CLUTCH SYSTEM

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

GREASE POINTS/NIPPLES

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 12,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26

STEERING BOX

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.