JEEP CHEROKEE SJ CHEROKEE V8 QUADRA-TRAC 360 (1980-1983)



ENGINE 360 Capacity: 4,7 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Racing Oil 15W-50		
Check every 1000 km, change every 12	2000 km/ 8 months	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Classic Multigrade 15W-40	Classic Multigrade 10W-30

Check every 1000 km, change every 12000 km/8 months

DIFFERENTIAL FRONT Capacity: 1,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	
Check every 8000 km, change every 48000 km	'

DIFFERENTIAL REAR Capacity: 2,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	
Check every 8000 km, change every 48000 km	·

DIFFERENTIAL REAR Trac-Lok
Capacity: 2,3 liter

USE CLIMATE
Normal Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90

Check every 8000 km, change every 48000 km

JEEP CHEROKEE SJ CHEROKEE V8 QUADRA-TRAC 360 (1980-1983)



TRANSFERBOX Quadra-Trac Capacity: 1,9 liter		
USE		CLIMATE
Filled for life		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Asyntho 5W-30	Classic Multigrade 10W-30	

USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
ATF Dexron II-D			
Check every 8000 km, change every 4	0000 km		
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1			
ATF Dexron II-D			

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 8000 km	

POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	Classic ATF A	
Check every 8000 km	·	·

JEEP CHEROKEE SJ CHEROKEE V8 QUADRA-TRAC 360 (1980-1983)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 24000 km	,	'

COOLING SYSTEM Capacity: 13,2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Change every 40000 km/25 months	3	1	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.