## **JENSEN C-V8 C-V8 MK III** (1965-1966)



Classic Monograde 30

ENGINE Capacity: 4,7 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Multigrade 15W-40		
Check every 8 km, change every 6500	km/ 6 months	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

Classic Multigrade 10W-30

Check every 8 km, change every 6500 km/6 months

**HDX 10W** 

DIFFERENTIAL REAR Capacity: 1,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	

Check every 6500 km, change every 19500 km

<b>TRANSMISSION AUTOMATIC</b> 3/1 Capacity: 9,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Classic ATF A			
01 1 100001 10 11	540001 /04	-	

Check every 13000 km/ 6 months, change every 51000 km/ 24 months

TRANSMISSION MANUAL WITH OVERD Capacity: 3,3 liter	VE 4/1
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic ATF A	
Check every 13000 km/ 6 months	

## **JENSEN C-V8 C-V8 MK III** (1965-1966)



HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 3250 km		

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		

Check every 1500 km

COOLING SYSTEM Capacity: 18,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every Daily, change every 80	00 km	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.

Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.