

LAND ROVER (EU) SERIES II/IIA 88/109

SERIES IIA 109 (1961-1971)

**ENGINE**

Capacity: 6 liter

USE

Normal road conditions

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Change every 5000 km/ 120 hours*

USE

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Change every 2500 km/ 60 hours***DIFFERENTIAL FRONT ENV**

Capacity: 1,4 liter

USE

Normal road conditions

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 5000 km/ 120 hours, change every 15000 km/ 360 hours*

USE

Normal road conditions

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 5000 km/ 120 hours, change every 15000 km/ 360 hours*

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Change every 1 months*

USE

Severe

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Change every 1 months*

LAND ROVER (EU) SERIES II/IIA 88/109

SERIES IIA 109 (1961-1971)



USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

Change every 2500 km/ 60 hours

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		

Change every 2500 km/ 60 hours

DIFFERENTIAL FRONT LIMITED SLIP

Capacity: 1,75 liter

USE		CLIMATE
Normal road conditions		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear LS 90		

Check every 5000 km/ 120 hours, change every 15000 km/ 360 hours

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear LS 90		

Change every 1 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear LS 90		

Change every 2500 km/ 60 hours

DIFFERENTIAL FRONT STANDARD

Capacity: 1,75 liter

USE		CLIMATE
Normal road conditions		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

Check every 5000 km/ 120 hours, change every 15000 km/ 360 hours

LAND ROVER (EU) SERIES II/IIA 88/109

SERIES IIA 109 (1961-1971)



USE		CLIMATE
Normal road conditions		Arctic
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		
<i>Check every 5000 km/ 120 hours, change every 15000 km/ 360 hours</i>		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
<i>Change every 1 months</i>		
USE		CLIMATE
Severe		Arctic
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		
<i>Change every 1 months</i>		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
<i>Change every 2500 km/ 60 hours</i>		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		
<i>Change every 2500 km/ 60 hours</i>		
DIFFERENTIAL REAR ENV		
Capacity: 1,2 liter		
USE		CLIMATE
Normal road conditions		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
<i>Check every 5000 km/ 120 hours, change every 15000 km/ 360 hours</i>		
USE		CLIMATE
Normal road conditions		Arctic
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		
<i>Check every 5000 km/ 120 hours, change every 15000 km/ 360 hours</i>		

LAND ROVER (EU) SERIES II/IIA 88/109

SERIES IIA 109 (1961-1971)



USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
<i>Change every 1 months</i>		
USE		CLIMATE
Severe		Arctic
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		
<i>Change every 1 months</i>		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
<i>Change every 2500 km/ 60 hours</i>		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		
<i>Change every 2500 km/ 60 hours</i>		
DIFFERENTIAL REAR LIMITED SLIP		
Capacity: 1,75 liter		
USE		CLIMATE
Normal road conditions		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear LS 90		
<i>Check every 5000 km/ 120 hours, change every 15000 km/ 360 hours</i>		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear LS 90		
<i>Change every 1 months</i>		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear LS 90		
<i>Change every 2500 km/ 60 hours</i>		

LAND ROVER (EU) SERIES II/IIA 88/109

SERIES IIA 109 (1961-1971)



DIFFERENTIAL REAR STANDARD

Capacity: 1,75 liter

USE	CLIMATE
Normal road conditions	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 5000 km/ 120 hours, change every 15000 km/ 360 hours*

USE	CLIMATE
Normal road conditions	Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 5000 km/ 120 hours, change every 15000 km/ 360 hours*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Change every 1 months*

USE	CLIMATE
Severe	Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Change every 1 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Change every 2500 km/ 60 hours*

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Change every 2500 km/ 60 hours*

TRANSFERBOX WITH LOW RANGE TRANSMISSION

Capacity: 2,5 liter

LAND ROVER (EU) SERIES II/IIA 88/109

SERIES IIA 109 (1961-1971)



USE	CLIMATE
Normal road conditions	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 5000 km/ 120 hours, change every 15000 km/ 360 hours*

USE	CLIMATE
Normal road conditions	Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 5000 km/ 120 hours, change every 15000 km/ 360 hours*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Change every 1 months*

USE	CLIMATE
Severe	Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Change every 1 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Change every 2500 km/ 60 hours*

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Change every 2500 km/ 60 hours***TRANSMISSION MANUAL 4/1**

Capacity: 1,5 liter

USE	CLIMATE
Normal road conditions	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 5000 km/ 120 hours, change every 15000 km/ 360 hours*

LAND ROVER (EU) SERIES II/IIA 88/109

SERIES IIA 109 (1961-1971)



USE		CLIMATE
Normal road conditions		Arctic
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		

Check every 5000 km/ 120 hours, change every 15000 km/ 360 hours

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

Change every 1 months

USE		CLIMATE
Severe		Arctic
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		

Change every 1 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

Change every 2500 km/ 60 hours

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		

Change every 2500 km/ 60 hours

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal road conditions		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 5000 km/ 120 hours

LAND ROVER (EU) SERIES II/IIA 88/109

SERIES IIA 109 (1961-1971)



HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal road conditions		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 5000 km/ 120 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal road conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 10,8 liter

USE		CLIMATE
Normal road conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

HYDRAULIC WINCH GEARBOX

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		

HYDRAULIC WINCH SUPPLY TANK

Capacity: 20 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 32		

LAND ROVER (EU) SERIES II/IIA 88/109

SERIES IIA 109 (1961-1971)



STEERING BOX

USE

Normal road conditions

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 5000 km/ 120 hours*

USE

Normal road conditions

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 5000 km/ 120 hours*

WINCH Capstan

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90

USE

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.