

MERCEDES-BENZ (EU) 123-SERIEN W123

300CD 123.150 (1977-1979)



MOTOR OM617.912

Kapacitet: 6,5 liter (Servicepåfyldning), Kapacitet: 7,5 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 10W-40	Bi-Turbo 20W-50	Bi-Turbo 15W-40

Kontroller alle 500 km, skift alle 7500 km/ 6 måneder

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Asyntho 5W-30		

Kontroller alle 500 km, skift alle 7500 km/ 6 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 10W-40	Bi-Turbo 20W-50	Bi-Turbo 15W-40

Skift alle 3500 km

ANVEND	KLIMA
Krævende	Koldt

PRODUKTANBEFALING 1		
Asyntho 5W-30		

Skift alle 3500 km

DIFFERENTIALE BAG

Kapacitet: 1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Classic Gear MP 90		

Kontroller alle 15000 km/ 12 måneder

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1		
Classic Gear MP 90		

Skift alle 7500 km

MERCEDES-BENZ (EU) 123-SERIEN W123

300CD 123.150 (1977-1979)



GEAR AUTOMATISK 722.1xx 4/1
Kapacitet: 4,8 liter (Servicepåfyldning), Kapacitet: 6,1 liter (Tør efterfyld)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
ATF Dexron II-D

Kontroller alle 1500 km/ 12 måneder, skift alle 45000 km

ANVEND
Krævende

KLIMA
Moderat

PRODUKTANBEFALING 1
ATF Dexron II-D

Skift alle 22500 km

HYDRAULISK NIVELLERINGSSYSTEM
Kapacitet: 4,2 liter (Metalreservoir), Kapacitet: 3,5 liter (Plastiksump)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Fluid 3023

Kontroller alle 15000 km/ 12 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM
Kapacitet: 0,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-S DOT 4

Kontroller alle 500 km, skift alle 12 måneder

SERVOSTYRING
Kapacitet: 1,4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Classic ATF A

Kontroller alle 15000 km/ 12 måneder

MERCEDES-BENZ (EU) 123-SERIEN W123

300CD 123.150 (1977-1979)



KØLESYSTEM

Kapacitet: 11 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 11

Kontroller alle 500 km, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.