

MERCEDES-BENZ (EU) S-KLASSE W116 / 126 280 SE, SEL 126.022/023 (1981-1985)



MOTOR M110.989

Kapacitet: 6 liter (Servicepåfyldning), Kapacitet: 7 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Classic Racing Oil 15W-50	Classic Multigrade 20W-50	Classic Multigrade 15W-40

Kontroller alle 500 km, skift alle 10000 km/ 12 måneder

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Asyntho 5W-30	Classic Multigrade 10W-30	

Kontroller alle 500 km, skift alle 10000 km/ 12 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Classic Racing Oil 15W-50	Classic Multigrade 20W-50	Classic Multigrade 15W-40

Skift alle 5000 km

ANVEND	KLIMA
Krævende	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Asyntho 5W-30	Classic Multigrade 10W-30	

Skift alle 5000 km

DIFFERENTIALE BAG

Kapacitet: 1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Classic Gear MP 90		

Kontroller alle 20000 km/ 24 måneder

MERCEDES-BENZ (EU) S-KLASSE W116 / 126 280 SE, SEL 126.022/023 (1981-1985)



GEAR AUTOMATISK 722.3xx 4/1
Kapacitet: 6,2 liter (Servicepåfyldning), Kapacitet: 7,3 liter (Tør efterfyld)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
ATF Dexron II-D

Kontroller alle 20000 km/ 24 måneder, skift alle 60000 km

ANVEND
Krævende

KLIMA
Moderat

PRODUKTANBEFALING 1
ATF Dexron II-D

Skift alle 30000 km

GEAR MANUEL 716.0xx 4/1
Kapacitet: 1,6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Classic ATF A

Kontroller alle 20000 km/ 24 måneder

ANVEND
Første skift kun

KLIMA
Moderat

PRODUKTANBEFALING 1
Classic ATF A

Skift alle 10000 km

GEAR MANUEL 717.4xx 5/1
Kapacitet: 1,6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Classic ATF A

Kontroller alle 20000 km/ 24 måneder

ANVEND
Første skift kun

KLIMA
Moderat

PRODUKTANBEFALING 1
Classic ATF A

Skift alle 10000 km

MERCEDES-BENZ (EU) S-KLASSE W116 / 126 280 SE, SEL 126.022/023 (1981-1985)



HYDRAULISK NIVELLERINGSSYSTEM

Kapacitet: 4,2 liter (Metalreservoir), Kapacitet: 3,5 liter (Plastiksump)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3023

Kontroller alle 20000 km/ 24 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-S DOT 4

Kontroller alle 500 km, skift alle 12 måneder

SERVOSTYRING

Kapacitet: 1,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic ATF A

Kontroller alle 20000 km/ 24 måneder

KØLESYSTEM

Kapacitet: 10,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 11

Kontroller alle 500 km, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.