

# MERCEDES-BENZ (EU) SL / SLC R107 / C107 450 SLC 107.024 (1973-1974)



## MOTOR M117.982

Kapacitet: 8 liter (Servicepåfyldning), Kapacitet: 9 liter (Tør efterfyld)

| ANVEND                           |                                  | KLIMA                            |
|----------------------------------|----------------------------------|----------------------------------|
| Normal                           |                                  | Moderat                          |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2              | PRODUKTANBEFALING 3              |
| <b>Classic Racing Oil 15W-50</b> | <b>Classic Multigrade 20W-50</b> | <b>Classic Multigrade 15W-40</b> |

Kontroller alle 500 km, skift alle 10000 km/ 12 måneder

| ANVEND               |                                  | KLIMA |
|----------------------|----------------------------------|-------|
| Normal               |                                  | Koldt |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2              |       |
| <b>Asyntho 5W-30</b> | <b>Classic Multigrade 10W-30</b> |       |

Kontroller alle 500 km, skift alle 10000 km/ 12 måneder

## DIFFERENTIALE BAG

Kapacitet: 1,3 liter

| ANVEND                    |  | KLIMA   |
|---------------------------|--|---------|
| Normal                    |  | Moderat |
| PRODUKTANBEFALING 1       |  |         |
| <b>Classic Gear MP 90</b> |  |         |

## GEAR AUTOMATISK 722.0xx 3/1

Kapacitet: 7,9 liter (Servicepåfyldning), Kapacitet: 8,9 liter (Tør efterfyld)

| ANVEND                 |  | KLIMA   |
|------------------------|--|---------|
| Normal                 |  | Moderat |
| PRODUKTANBEFALING 1    |  |         |
| <b>ATF Dexron II-D</b> |  |         |

## SELVSPÆRRENDE DIFFERENTIALE BAG

Kapacitet: 1,3 liter

| ANVEND                    |  | KLIMA   |
|---------------------------|--|---------|
| Normal                    |  | Moderat |
| PRODUKTANBEFALING 1       |  |         |
| <b>Classic Gear LS 90</b> |  |         |

# MERCEDES-BENZ (EU) SL / SLC R107 / C107 450 SLC 107.024 (1973-1974)



## HYDRAULISK NIVELLERINGSSYSTEM

Kapacitet: 4,2 liter (Metalreservoir), Kapacitet: 3,5 liter (Plastiksump)

| ANVEND               |  | KLIMA   |
|----------------------|--|---------|
| Normal               |  | Moderat |
| PRODUKTANBEFALING 1  |  |         |
| <b>SP Fluid 3023</b> |  |         |

## HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,5 liter

| ANVEND                    |  | KLIMA   |
|---------------------------|--|---------|
| Normal                    |  | Moderat |
| PRODUKTANBEFALING 1       |  |         |
| <b>Drauliquid-S DOT 4</b> |  |         |

## SERVOSTYRING

Kapacitet: 1,4 liter

| ANVEND               |  | KLIMA   |
|----------------------|--|---------|
| Normal               |  | Moderat |
| PRODUKTANBEFALING 1  |  |         |
| <b>Classic ATF A</b> |  |         |

## KØLESYSTEM

Kapacitet: 15 liter

| ANVEND               |  | KLIMA   |
|----------------------|--|---------|
| Normal               |  | Moderat |
| PRODUKTANBEFALING 1  |  |         |
| <b>Coolant SP 11</b> |  |         |

Skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.