

# MERCEDES-BENZ (EU) 123 SERIES W123

## 230T 123.083 (1978-1980)

**ENGINE** M115.954

Capacity: 6 liter (Dry fill), Capacity: 5,5 liter (Service fill), Filter capacity: 0,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2         | PRODUCT RECOMMENDATION 3         |
|----------------------------------|----------------------------------|----------------------------------|
| <b>Classic Racing Oil 15W-50</b> | <b>Classic Multigrade 20W-50</b> | <b>Classic Multigrade 15W-40</b> |

*Check every 500 km, change every 7500 km/ 6 months*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2         | PRODUCT RECOMMENDATION 3 |
|--------------------------|----------------------------------|--------------------------|
| <b>Asyntho 5W-30</b>     | <b>Classic Multigrade 10W-30</b> |                          |

*Check every 500 km, change every 7500 km/ 6 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2         | PRODUCT RECOMMENDATION 3         |
|----------------------------------|----------------------------------|----------------------------------|
| <b>Classic Racing Oil 15W-50</b> | <b>Classic Multigrade 20W-50</b> | <b>Classic Multigrade 15W-40</b> |

*Change every 3500 km*

| USE    | CLIMATE |
|--------|---------|
| Severe | Cold    |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2         | PRODUCT RECOMMENDATION 3 |
|--------------------------|----------------------------------|--------------------------|
| <b>Asyntho 5W-30</b>     | <b>Classic Multigrade 10W-30</b> |                          |

*Change every 3500 km***DIFFERENTIAL REAR**

Capacity: 1 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---------------------------|--------------------------|--------------------------|
| <b>Classic Gear MP 90</b> |                          |                          |

*Check every 15000 km/ 12 months*

| USE               | CLIMATE  |
|-------------------|----------|
| First change only | Moderate |

| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---------------------------|--------------------------|--------------------------|
| <b>Classic Gear MP 90</b> |                          |                          |

*Change every 7500 km*

# MERCEDES-BENZ (EU) 123 SERIES W123

## 230T 123.083 (1978-1980)



**TRANSMISSION AUTOMATIC** 722.1xx 4/1  
Capacity: 6,1 liter (Dry fill), Capacity: 4,8 liter (Service fill)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Classic ATF A**

*Check every 1500 km/ 12 months, change every 45000 km*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

**Classic ATF A**

*Change every 22500 km*

**TRANSMISSION MANUAL** 716.0xx 4/1  
Capacity: 1,6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Classic ATF A**

*Check every 15000 km/ 12 months*

| USE               | CLIMATE  |
|-------------------|----------|
| First change only | Moderate |

PRODUCT RECOMMENDATION 1

**Classic ATF A**

*Change every 7500 km*

**HYDRAULIC LEVELLING SYSTEM**  
Capacity: 3,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Fluid 3023**

*Check every 15000 km/ 12 months*

# MERCEDES-BENZ (EU) 123 SERIES W123

## 230T 123.083 (1978-1980)



### HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,6 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Drauliquid DOT 3</b>  |  |          |

Check every 500 km, change every 12 months

### POWER STEERING

Capacity: 1,4 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Classic ATF A</b>     |  |          |

Check every 15000 km/ 12 months

### COOLING SYSTEM

Capacity: 10 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 11</b>     |  |          |

Check every 500 km, change every 24 months

### STEERING BOX

Capacity: 0,3 liter

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Normal                    |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Classic Gear MP 90</b> |  |          |

Check every 15000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.