

# MERCEDES-BENZ (EU) 300 SL W198 / R198 (GULL-WING + ROADSTER) 300 SL (1954-1957)



**ENGINE** M198  
Capacity: 11-15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Classic Multigrade 10W-30</b>	<b>Classic Monograde 30</b>	

*Change every 3000 km/ 6 months*

## DIFFERENTIAL REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Classic Gear LS 90</b>		

*Change every 18000 km*

## TRANSMISSION MANUAL 4/1

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Classic ATF A</b>		

*Change every 18000 km*

## HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

## COOLING SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

# MERCEDES-BENZ (EU) 300 SL W198 / R198 (GULL-WING + ROADSTER) 300 SL (1954- 1957)

**STEERING BOX**

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Classic Gear MP 90**

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*