

MERCEDES-BENZ (EU) S-CLASS W116 / 126

450 SE, SEL 116.032/033 (1972-1980)

**ENGINE** M117.98x

Capacity: 8 liter, Capacity: 8,5 liter (Dry fill), Capacity: 9 liter (Dry fill, with oil cooler), Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Multigrade 20W-50*Change every 7500 km/ 6 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40*Change every 7500 km/ 6 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30*Change every 7500 km/ 6 months*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Multigrade 20W-50*Change every 3750 km/ 6 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40*Change every 3750 km/ 6 months*

USE	CLIMATE
Severe	Cold

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30*Change every 3750 km/ 6 months*

MERCEDES-BENZ (EU) S-CLASS W116 / 126

450 SE, SEL 116.032/033 (1972-1980)

**DIFFERENTIAL REAR**

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 7500 km/ 6 months*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 7500 km/ 6 months***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear LS 90*Check every 7500 km/ 6 months*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear LS 90*Check every 7500 km/ 6 months*

MERCEDES-BENZ (EU) S-CLASS W116 / 126

450 SE, SEL 116.032/033 (1972-1980)

**TRANSMISSION AUTOMATIC 722.0xx 3/1**

Capacity: 7,9 liter (Change capacity), Capacity: 8,9 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 7500 km/ 6 months, change every 45000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 3750 km/ 6 months, change every 22500 km*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 7500 km/ 6 months, change every 45000 km*

USE	CLIMATE
Severe (alternative)	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 3750 km/ 6 months, change every 22500 km***HYDRAULIC LEVELLING SYSTEM**

Capacity: 4,2 liter (Metal reservoir), Capacity: 3,5 liter (Plastic reservoir)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3023*Check every 7500 km/ 6 months*

MERCEDES-BENZ (EU) S-CLASS W116 / 126

450 SE, SEL 116.032/033 (1972-1980)



HYDRAULIC BRAKE SYSTEM

Capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4*Change every 12 months*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Change every 12 months*

POWER STEERING LS 90

Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 7500 km/ 6 months*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 7500 km/ 6 months*

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease*Check every 7500 km/ 6 months*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 7500 km/ 6 months*

MERCEDES-BENZ (EU) S-CLASS W116 / 126

450 SE, SEL 116.032/033 (1972-1980)

**COOLING SYSTEM**

Capacity: 14 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 11

Check every 7500 km/ 6 months

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26

Check every 7500 km/ 6 months

AIRCONDITIONING COMPRESSOR

Capacity: 30 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.