MERCEDES-BENZ (EU) SL / SLC R107 / C107 420 SL 107.047 (1985-1989)



| ENGINE M116.E42 Capacity: 8 liter, Filter capacity: 1,5 liter | | |
|---|--------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Bi-Turbo 20W-50 | | |
| Check every 3000 km, change every 1000 | 00 km/ 12 months | · |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Emperol 10W-40 | Bi-Turbo 15W-40 | |
| Check every 3000 km, change every 1000 | 00 km/ 12 months | |
| USE | | CLIMATE |
| Severe | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Bi-Turbo 20W-50 | | |
| Change every 5000 km/ 6 months | | |
| USE | | CLIMATE |
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Emperol 10W-40 | Bi-Turbo 15W-40 | |
| Change every 5000 km/ 6 months | | |
| | | |
| DIFFERENTIAL REAR | | |

| DIFFERENTIAL REAR Capacity: 1,3 liter | | | |
|--|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Classic Gear LS 90 | Classic Gear MP 90 | | |

Check every 20000 km, change every 10000 km

| DIFFERENTIAL REAR LIMITED SLIP Capacity: 1,3 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Classic Gear LS 90 | |
| Check every 20000 km | |

MERCEDES-BENZ (EU) SL / SLC R107 / C107 420 SL 107.047 (1985-1989)



| ATF Dexron II-D | ATF Almirol | | |
|--|--------------------------|----------|--|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Severe | | Moderate | |
| USE | | CLIMATE | |
| Check every 20000 km, change every 60000 km | | | |
| ATF Dexron II-D | ATF Almirol | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Normal | | Moderate | |
| USE | | CLIMATE | |
| TRANSMISSION AUTOMATIC 722.3xx 4/1 Capacity: 7,7 liter | | | |

| HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,5 liter | | |
|---|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid-S DOT 4 | | |

Check every 20000 km, change every 12 months

Check every 20000 km, change every 30000 km

| POWER STEERING Capacity: 1,4 liter | |
|------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Classic ATF A | |
| Check every 20000 km | |

| GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT | | |
|--|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| Labora Grease | | |
| Check every 20000 km | | |

MERCEDES-BENZ (EU) SL / SLC R107 / C107 420 SL 107.047 (1985-1989)



| COOLING SYSTEM Capacity: 12,5 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 11 | | |
| Check every 20000 km, change every 36 months | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.