

MERCEDES-BENZ (EU) SL / SLC R107 / C107 450 SLC 5.0 107.026 (1980-1981)

**ENGINE** M117.960

Capacity: 9 liter (Dry fill), Capacity: 8 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Racing Oil 15W-50	Classic Multigrade 20W-50	Classic Multigrade 15W-40

Check every 500 km, change every 10000 km/ 12 months

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Asyntho 5W-30	Classic Multigrade 10W-30	

*Check every 500 km, change every 10000 km/ 12 months***DIFFERENTIAL REAR**

Capacity: 1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		

DIFFERENTIAL REAR LIMITED SLIP

Capacity: 1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear LS 90		

TRANSMISSION AUTOMATIC 722.3xx 4/1

Capacity: 8,6 liter (Dry fill), Capacity: 7,7 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

MERCEDES-BENZ (EU) SL / SLC R107 / C107 450 SLC 5.0 107.026 (1980-1981)



HYDRAULIC LEVELLING SYSTEM

Capacity: 4,2 liter (Metal reservoir), Capacity: 3,5 liter (Plastic sump)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3023		

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

POWER STEERING

Capacity: 1,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF A		

COOLING SYSTEM

Capacity: 13,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.