

# MITSUBISHI (EU) CELESTE CELESTE 2000 A78 (1975-1980)



## MOTOR 4G52

Kapacitet: 4,3 liter, Filterkapacitet: 0,5 liter

### ANVEND

Normal

### KLIMA

Middelhavsagtigt

#### PRODUKTANBEFALING 1

**Classic Multigrade 20W-50**

*Skift alle 10000 km*

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Classic Racing Oil 15W-50**

#### PRODUKTANBEFALING 2

**Classic Multigrade 15W-40**

#### PRODUKTANBEFALING 3

**Classic Multigrade 10W-30**

*Skift alle 10000 km*

### ANVEND

Første Service

### KLIMA

Middelhavsagtigt

#### PRODUKTANBEFALING 1

**Classic Multigrade 20W-50**

*Skift alle 1000 km*

### ANVEND

Første Service

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Classic Racing Oil 15W-50**

#### PRODUKTANBEFALING 2

**Classic Multigrade 15W-40**

#### PRODUKTANBEFALING 3

**Classic Multigrade 10W-30**

*Skift alle 1000 km*

## DIFFERENTIALE BAG

Kapacitet: 1,1 liter

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Classic Gear EP 90**

*Kontroller alle 20000 km, skift alle 80000 km*

# MITSUBISHI (EU) CELESTE CELESTE 2000

## A78 (1975-1980)



### GEAR AUTOMATISK 3/1

Kapacitet: 6,4 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1    |  |  |
|------------------------|--|--|
| <b>ATF Dexron II-D</b> |  |  |

Kontroller alle 20000 km, skift alle 80000 km

| ANVEND   | KLIMA   |
|----------|---------|
| Krævende | Moderat |

| PRODUKTANBEFALING 1    |  |  |
|------------------------|--|--|
| <b>ATF Dexron II-D</b> |  |  |

Kontroller alle 20000 km, skift alle 40000 km

### GEAR MANUEL 4/1

Kapacitet: 1,7 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1       |  |  |
|---------------------------|--|--|
| <b>Classic Gear EP 80</b> |  |  |

Kontroller alle 20000 km, skift alle 40000 km

### GEAR MANUEL 5/1

Kapacitet: 2,3 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1       |  |  |
|---------------------------|--|--|
| <b>Classic Gear EP 80</b> |  |  |

Kontroller alle 20000 km, skift alle 40000 km

### HYDRAULISK BREMSESYSTEM

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1     |  |  |
|-------------------------|--|--|
| <b>Drauliquid DOT 3</b> |  |  |

Skift alle 20000 km/ 12 måneder

# MITSUBISHI (EU) CELESTE CELESTE 2000 A78 (1975-1980)



## SMØREPUNKTER/NIPLER

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## SMØREPUNKTER/NIPLER HJULLEJER

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

*Skift alle 60000 km*

## KØLESYSTEM

Kapacitet: 6,5 liter

| ANVEND                        |  | KLIMA   |
|-------------------------------|--|---------|
| Normal                        |  | Moderat |
| PRODUKTANBEFALING 1           |  |         |
| <b>Coolant -38 Organic NF</b> |  |         |

*Skift alle 40000 km/ 24 måneder*

## STYREHUS

Kapacitet: 0,18 liter

| ANVEND                    |  | KLIMA   |
|---------------------------|--|---------|
| Normal                    |  | Moderat |
| PRODUKTANBEFALING 1       |  |         |
| <b>Classic Gear EP 90</b> |  |         |

*Kontroller alle 40000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.