MORRIS MARINA ADO28 MARINA 1.3 (1975-1980)



ENGINE 12V Capacity: 3,7 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Multigrade 20W-50		
Change every 10000 km/ 6 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Racing Oil 15W-50	Classic Multigrade 15W-40	Classic Multigrade 10W-30
Change every 10000 km/ 6 months		

DIFFERENTIAL REAR Capacity: 0,71 liter		
USE	CL	IMATE
Normal	M	loderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		
Check every 10000 km/ 6 months		

TRANSMISSION AUTOMATIC 3/1 Capacity: 6,54 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic ATF F	
Check every 10000 km/ 6 months	·

TRANSMISSION MANUAL 4/1 Capacity: 0,85 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	
Check every 10000 km/ 6 months	·

MORRIS MARINA ADO28 MARINA 1.3 (1975-1980)



HYDRAULIC BRAKE SYSTEM		
use Normal		climate Moderate
		Moderate
PRODUCT RECOMMENDATION 1 Drauliquid DOT 3		
Check every 5000 km/ 3 months		
GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 10000 km/ 6 months	•	· ·
COOLING SYSTEM		
Capacity: 4,26 liter (+ heater)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
CARBURETTOR DAMPER		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Multigrade 20W-50		
Check every 10000 km/ 6 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Multigrade 15W-40		
Check every 10000 km/ 6 months		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

Classic Multigrade 10W-30
Check every 10000 km/ 6 months

PRODUCT RECOMMENDATION

MORRIS MARINA ADO28 MARINA 1.3 (1975-1980)



information contained herein is subject to changes without notification.