

MORRIS OXFORD OXFORD DIESEL SALOON SERIES VI (1961-1966)



ENGINE 15X
Capacity: 4,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Classic Multigrade 10W-30	Classic Monograde 30

Change every 5000 km

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	
HDX 10W	

Change every 5000 km

DIFFERENTIAL REAR
Capacity: 1,28 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Classic Gear EP 90	

Check every 5000 km, change every 10000 km

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	
Classic Gear EP 80	

Check every 5000 km, change every 10000 km

TRANSMISSION MANUAL 4/1
Capacity: 2,56 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Classic Multigrade 10W-30	Classic Monograde 30

Check every 5000 km, change every 10000 km

MORRIS OXFORD OXFORD DIESEL SALOON SERIES VI (1961-1966)



HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 5000 km

GREASE POINTS/NIPPLES WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 10000 km

COOLING SYSTEM

Capacity: 5,4 liter (+ heater), Capacity: 5,1 liter (Without heater)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

CARBURETTOR DAMPER

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Monograde 30		

Change every 5000 km

MORRIS OXFORD OXFORD DIESEL SALOON SERIES VI (1961-1966)



STEERING BOX

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 5000 km*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 5000 km*

WATER PUMP

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.