

OPEL ADMIRAL ADMIRAL 2.8 E (1969-1977)



MOTOR 28E
Kapacitet: 4,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Classic Racing Oil 15W-50

PRODUKTANBEFALING 2
Classic Multigrade 20W-50

PRODUKTANBEFALING 3
Classic Multigrade 15W-40

Skift alle 5000 km/ 3 måneder

ANVEND
Normal

KLIMA
Arktisk

PRODUKTANBEFALING 1
HDX 10W

Skift alle 5000 km/ 3 måneder

DIFFERENTIALE BAG
Kapacitet: 1,3 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Classic Gear MP 90

Kontroller alle 10000 km/ 6 måneder

GEAR AUTOMATISK 3/1
Kapacitet: 2,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Classic ATF A

Kontroller alle 10000 km/ 6 måneder, skift alle 40000 km/ 24 måneder

GEAR MANUEL 4/1
Kapacitet: 1,1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Classic Gear EP 80

Kontroller alle 10000 km/ 6 måneder

OPEL ADMIRAL ADMIRAL 2.8 E (1969-1977)



SELVSPÆRRENDE DIFFERENTIALE BAG

Kapacitet: 1,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Gear LS 90

Kontroller alle 10000 km/ 6 måneder

HYDRAULISK BREMSESYSYSTEM

Kapacitet: 0,42 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Skift alle 20000 km

HYDRAULISK KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Skift alle 20000 km

SERVOSTYRING

Kapacitet: 1,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic ATF A

KØLESYSTEM

Kapacitet: 8,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.