OPEL ASCONA B ASCONA 1.9S (1975-1977)



ENGINE 19S Capacity: 3,8 liter, Filter capacity: 0,3 li	iter	
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Classic Racing Oil 15W-50	PRODUCT RECOMMENDATION 2 Classic Multigrade 20W-50	PRODUCT RECOMMENDATION 3 Classic Multigrade 15W-40
Change every 10000 km/ 6 months		
use Initial service		climate Moderate
PRODUCT RECOMMENDATION 1 Classic Racing Oil 15W-50	PRODUCT RECOMMENDATION 2 Classic Multigrade 20W-50	PRODUCT RECOMMENDATION 3 Classic Multigrade 15W-40
Change every 1000 km		

AXLE REAR Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		
Check every 10000 km/ 6 months		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube RPC 75W-80	SP Gear 5015	
Check every 10000 km/ 6 months		

TRANSMISSION AUTOMATIC GM 3-OVH 3/1 Capacity: 2,5 liter (Service fill)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
ATF Dexron II-D			

OPEL ASCONA B ASCONA 1.9S (1975-1977)



TRANSMISSION MANUAL 4/1 Capacity: 1,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear EP 80	
Check every 10000 km/ 6 months	

HYDRAULIC BRAKE SYSTEM Capacity: 0,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

WHEEL BEARINGS FRONT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 6,1 liter, Capacity: 7 liter (with automatic transmission)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.