

OPEL MANTA B MANTA 2.0 GT/E (1977-1981)**ENGINE 20E**

Capacity: 3,8 liter, Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Racing Oil 15W-50	Classic Multigrade 20W-50	Classic Multigrade 15W-40

Change every 10000 km/ 6 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Racing Oil 15W-50	Classic Multigrade 20W-50	Classic Multigrade 15W-40

*Change every 1000 km***AXLE REAR**

Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		

Check every 10000 km/ 6 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube RPC 75W-80	SP Gear 5015	

*Check every 10000 km/ 6 months***TRANSMISSION AUTOMATIC GM 3-OVH 3/1**

Capacity: 2,5 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

OPEL MANTA B MANTA 2.0 GT/E (1977-1981)**TRANSMISSION MANUAL 4/1**

Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		

Check every 10000 km/ 6 months

HYDRAULIC BRAKE SYSTEM

Capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

WHEEL BEARINGS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 6,2 liter, Capacity: 6,1 liter (with automatic transmission)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.