

# PEUGEOT 305 581 305 1.8 DIESEL 581 M40/E40/U40 (1982-1988)

**ENGINE** XUD7 (161A)

Capacity: 5 liter

USE	CLIMATE
Normal	Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 15W-40***Check every 1000 km, change every 5000 km/ 6 months*

USE	CLIMATE
Normal	Arctic

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30***Check every 1000 km, change every 5000 km/ 6 months*

USE	CLIMATE
Severe	Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 15W-40***Check every 1000 km, change every 2500 km*

USE	CLIMATE
Severe	Arctic

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30***Check every 1000 km, change every 2500 km***TRANSAXLE MANUAL 4/1**

Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube RPC 75W-80**

## PRODUCT RECOMMENDATION 2

**SP Gear 5015***Change every 30000 km***TRANSAXLE MANUAL 5/1**

Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube RPC 75W-80**

## PRODUCT RECOMMENDATION 2

**SP Gear 5015***Change every 30000 km*

# PEUGEOT 305 581 305 1.8 DIESEL 581 M40/E40/U40 (1982-1988)



## HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Change every 45000 km/ 24 months*

## POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**ATF Dexron II-D**

## COOLING SYSTEM

Capacity: 9,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

PRODUCT RECOMMENDATION 2

**Coolant -26***Change every 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.