## **PEUGEOT 604 604 D TURBO** (1978-1985)



ENGINE XD2S Capacity: 5,5 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Monograde 30		
Check every 1000 km, change every 5000	km/ 6 months	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
HDX 10W		
Check every 1000 km, change every 5000 km/ 6 months		

DIFFERENTIAL REAR Capacity: 1,55 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	
Check every 5000 km, change every 30000 km	·

TRANSMISSION AUTOMATIC 3/1 Capacity: 5,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF A		
Check every 5000 km, change every 4500	km/ 24 months	

TRANSMISSION MANUAL 4/1 Capacity: 1,35 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Multigrade 15W-40		
Check every 5000 km, change every 30000 km		

## **PEUGEOT 604 604 D TURBO** (1978-1985)



TRANSMISSION MANUAL 5/1 Capacity: 1,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Multigrade 15W-40	
Check every 5000 km, change every 30000 km	

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	
Check every 5000 km, change every 45000 km/24 months	

POWER STEERING Capacity: 0,65 liter (Steering pump), Capacity: 0,79 liter (System)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 15000 km		

COOLING SYSTEM Capacity: 10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 5000 km/1 months, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.