RANGER (GM) RANGER B (II) 1700S (1972-1978)



USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Racing Oil 15W-50	Classic Multigrade 20W-50	Classic Multigrade 15W-40
Change every 10000 km/6 months		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
HDX 10W		
Change every 10000 km/ 6 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Racing Oil 15W-50	Classic Multigrade 20W-50	Classic Multigrade 15W-40
Change every 1000 km		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
HDX 10W		

Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	
Check every 10000 km/ 6 months	

DIFFERENTIAL REAR LIMITED SLIP		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Classic Gear LS 90		
Check every 10000 km/ 6 months		

RANGER (GM) RANGER B (II) 1700S (1972-1978)



TRANSMISSION AUTOMATIC 3/1 Capacity: 2,5 liter (Refill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF A		
01 1 100001 10 11 1	400001 /04 //	-

Check every 10000 km/6 months, change every 40000 km/24 months

TRANSMISSION MANUAL 4/1 Capacity: 1,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	
01 1 100001 10	:

Check every 10000 km/6 months

HYDRAULIC BRAKE SYSTEM Capacity: 0,37 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

Check every 5000 km/ 3 months, change every 40000 km/ 24 months

COOLING SYSTEM Capacity: 6,5 liter (Manual transmission), Capacity: 7,3 liter (with automatic transmission)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

STEERING BOX Capacity: 0,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear EP 90	
Check every 10000 km/ 6 months	·

PRODUCT RECOMMENDATION

RANGER (GM) RANGER B (II) 1700S (1972-1978)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.