

RELIANT SCIMITAR SE/SS SCIMITAR 1.4

SS1 (1986-1990)



ENGINE Ford CVH
Capacity: 3,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Classic Multigrade 15W-40	Classic Multigrade 10W-30

Change every 10000 km/ 6 months

REAR AXLE
Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Classic Gear EP 90	

Check every 20000 km/ 12 months

TRANSMISSION MANUAL 5/1
Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Classic Gear EP 80	

Check every 20000 km/ 12 months

HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

Change every 60000 km/ 36 months

COOLING SYSTEM
Capacity: 9,65 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Coolant -26	

Change every 40000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

RELIANT SCIMITAR SE/SS SCIMITAR 1.4 SS1 (1986-1990)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.