

# RELIANT SCIMITAR SE/SS SCIMITAR GTE

## 3.0 SE6/6A (1975-1980)



**ENGINE** Ford Essex  
Capacity: 5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Classic Racing Oil 15W-50</b>	<b>Classic Multigrade 20W-50</b>

*Change every 10000 km/ 6 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Classic Multigrade 15W-40</b>	<b>Classic Multigrade 10W-30</b>

*Change every 10000 km/ 6 months*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Classic Racing Oil 15W-50</b>	<b>Classic Multigrade 20W-50</b>

*Change every 1500 km*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Classic Multigrade 15W-40</b>	<b>Classic Multigrade 10W-30</b>

*Change every 1500 km*

**REAR AXLE**  
Capacity: 1,99 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>Classic Gear EP 90</b>	

*Check every 10000 km/ 6 months*

**TRANSMISSION AUTOMATIC 3/1**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>Classic ATF F</b>	

*Check every 10000 km/ 6 months*

# RELIANT SCIMITAR SE/SS SCIMITAR GTE

## 3.0 SE6/6A (1975-1980)

**TRANSMISSION MANUAL 4/1**

Capacity: 1,98 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Classic Gear EP 80**

Check every 10000 km/ 6 months, change every 20000 km/ 12 months

**TRANSMISSION MANUAL + OVERDRIVE 5/1**

Capacity: 2,84 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Classic Gear EP 80**

Check every 10000 km/ 6 months, change every 20000 km/ 12 months

**HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3**

Check every 3 months, change every 36000 km/ 18 months/ 6 months

**HYDRAULIC CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3**

Check every 3 months, change every 36000 km/ 18 months/ 6 months

**POWER STEERING**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Classic ATF F**

# RELIANT SCIMITAR SE/SS SCIMITAR GTE

## 3.0 SE6/6A (1975-1980)



### STEERING UNIT (POWERSTEERING)

Capacity: 0,06 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Classic Gear EP 90</b>		

### FRONT WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

Change every 60000 km

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

Change every 5000 km/ 3 months

### REAR WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

Change every 10000 km/ 6 months

### COOLING SYSTEM

Capacity: 9,65 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.