

RENAULT (EU) 15 / 17 R15 TL/GTL R1300 (1971-1977)



MOTOR

Kapacitet: 3,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Multigrade 15W-40

Skift alle 5000 km

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Classic Multigrade 10W-30

Skift alle 5000 km

TRANSAKSEL AUTOMATISK

Kapacitet: 3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 5000 km/ 6 måneder, skift alle 15000 km/ 12 måneder

TRANSAKSEL MANUEL 4/1

Kapacitet: 2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Gear EP 80

Kontroller alle 5000 km/ 6 måneder, skift alle 15000 km/ 12 måneder

TRANSAKSEL MANUEL 5/1

Kapacitet: 2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Gear MP 90

PRODUKTANBEFALING 2

Gearlube RPC 75W-80

PRODUKTANBEFALING 3

SP Gear 5015

Kontroller alle 5000 km/ 6 måneder, skift alle 15000 km/ 12 måneder

RENAULT (EU) 15 / 17 R15 TL/GTL R1300 (1971-1977)



HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

KØLESYSTEM

Kapacitet: 5,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.